

Lifetime Cancer Risk and Hazard Quotient of BTXs Compounds in Iranian Petrochemical and Petroleum Depot Workers

Razzagh Rahimpour¹, Sajjad Farhadi², Mahdi Jalali^{3*}

1) Department of Occupational Health, Centre of Health Researches, School of Public Health, Larestan School of Medical Sciences, Larestan, Iran.

2) Center of Excellence for Occupational Health (CEOH) and Research Center of Health Sciences, Hamadan University of Medical Sciences, Hamadan, IR, Iran

3) Department of Occupational Health Engineering, School of Public Health, Neyshabur University of Medical Sciences, Neyshabur, Iran

*Author for Correspondence: m.jalali@bums.ac.ir

Received: 24 Feb. 2017, Revised: 20 Jun. 2017, Accepted: 20 Jun. 2017

ABSTRACT

Exposing to the high-level of BTXs concentration can occur in the oil-dependent industries and may cause considerable adverse impacts on the health of employees. The main objective of the present study firstly is determining the exposure of petrochemical and oil depot workers to benzene, toluene, ortho and methyl xylenes, and p-xylene (BTXs), and secondly is estimating the lifetime cancer risk (LCR) and non-carcinogenic risk using the hazard quotient (HQ). This cross-sectional study is conducted on 85 workers at petrochemical (34 subjects) and oil depot (51 subjects) industries of Iran in 2016. In order to determine the exposure concentrations of BTXs, through inhaling way, individual sampling was carried out according to the NIOSH 1501 method. Then, estimating LCR of benzene, and non-carcinogenic risk of benzene, toluene, ortho and methyl xylenes, and p-xylene, using the HQ, has been conducted regards to criteria recommended by USEPA. The mean exposure concentration of benzene among the oil depot workers was higher than the petrochemical workers, but this difference was not statistically significant ($P = 0.162$). The mean exposure concentration of benzene in the oil depot workers ($2.1 \pm 2.53 \text{ mg/m}^3$) was higher than the occupational exposure limits provided by the American conference of governmental industrial hygienists ($\text{ACGIH_TLV} = 1.67 \text{ mg/m}^3$). The mean concentration of toluene in the exposed workers of the oil depot ($46.81 \pm 22.43 \text{ mg/m}^3$) was higher than the exposed workers of petrochemical ($41.83 \pm 30.06 \text{ mg/m}^3$), but this difference was not statistically significant ($P = 0.412$). The results of carcinogenic and non-carcinogenic risk assessment revealed high-risk exposure level in the both investigated groups. The mean LCR of benzene in the oil depot workers was higher than the petrochemical workers ($1.681\text{E-}3$ and $1.163\text{E-}3$, for the oil depot and petrochemical, respectively). The LCR of benzene and HQ of BTXs in the both investigated groups were higher than the reference values. In order to reduce occupational exposure to BTXs in the investigated oil depot and petrochemical, control measures should be taken in the future, as soon as possible.

Key words: Occupational Exposure; Risk Assessment; Workers; benzene; Toluene; Xylenes

List of abbreviations

VOCs	Volatile Organic Compounds
BTEX	Benzene, Toluene, Ethyl benzene and Xylenes
IARC	International Agency for Research on Cancer
WHO	World Health Organization
US EPA	United States Environmental Protection Agency
LCR	Lifetime Cancer Risk
HQ	Hazard Quotient
NIOSH	National Institute for Occupational Safety and Health
CDI	Chronic Daily Intake
SF	Slope Factor
IR	Inhalation Rate
ED	Exposure Duration
EF	Exposure Frequency
BW	Body Weight

AT	Average Time
NY	Number of Days per Year
RFD	Reference Dose Factor
NOAEL	No-Observable Averse Effect Level
UF	Uncertainty Factor
RfC	Reference Concentration Factor
ACGIH	American Conference of Governmental Industrial Hygienists
TLV	Threshold Limit Value

INTRODUCTION

Many chemical compounds such as heavy-chain hydrocarbons, light-chain volatile compounds, and short-chain organic compounds are mined, processed, produced and distributed through the oil-dependent industries. Some of these compounds have toxic properties and exposure to them can have adverse effects on human health. Toxic petroleum products are mainly light-chain volatile aromatic compounds [1]. The most important materials that are included in these products are Volatile Organic Compounds (VOCs) that are defined as organic compounds having a boiling point between 50°C and 260°C, and amongst VOCs, the most commonly found are benzene, toluene, ethyl benzene and xylenes (so-called BTEX) [2].

Adverse health effects caused by chronic exposure to VOCs are varied and can consider into two groups, carcinogenic and non- carcinogenic effects. Allergy, sensitization, and liver, kidney, nervous and respiratory disorders are viewed as non-carcinogenic effects [3-6]. Furthermore, lung, liver, kidney and biliary cancers and leukemia are some cases of carcinogenic effects [4, 7, 8]. Amongst BTEX, benzene is the most toxic compound, and prolonged exposure to a low concentration of it may lead to increase the incidence of leukemia and aplastic anemia in individuals who are exposed. The international agency for research on cancer (IARC) has classified benzene as a definite carcinogenic compound (Group I) [8]. Also, world health organization (WHO) has reported that prolonged exposure to 1.7µg/m³ of benzene causes leukemia in 10 people per million [9].

Oil-dependent chemical industries (e.g. Oil terminals, oil and gas transmission lines, petrochemicals, oil depots, refineries and etc.) generally are major industries that have a crucial role in mining, processing and distributing petroleum products. Petrochemicals and oil depots are two essential parts of oil-dependent chemical industries and much of the workforce is employed in these industries. Recently, several studies have been carried out for determining VOCs concentrations in the air of oil-dependent industries, especially BTEX concentrations, in order for determining environmental emissions and

occupational exposures. The results of these studies have suggested high emissions of these compounds into the environment. Also, occupational exposure to the VOCs has been reported in high values [10-14].

Recently, several studies carried out in Iran to survey the concentrations of BTEX in the air of petrochemicals, fuel stations (gasoline and gas), oil depots and urban air [15-21]. Although many international organizations such as the WHO, the united states environmental protection agency (US EPA) and the united states food and drug administration are using quantitative risk assessment for legislating on chemical compounds problems, but studies in Iran are mainly aimed to determine only exposure levels of BTEX and only a few studies are conducted on exposed workers of Iran's process industries for assessing carcinogenic quantitative risk and these studies have not been conducted in any oil depots [15, 18, 20, 22-24]. Furthermore, some conducted studies mainly have used semi-quantitative methods to evaluate the risk level of exposure to chemical substances; however, the validity of these methods is questionable [25-28]. Zare Jeddi *et al.* conducted a study to quantify the carcinogenic risk assessment of chemical substances in fuel stations. They found that the lifetime cancer risk was 3 out of 1,000 in occupied workers [29]. Also, Rahimnejad *et al.* determined the lifetime cancer risk in the petrochemical industry employees 3 out of 10,000, and the estimated health hazard of xylenes was higher than the reference value [24].

Therefore, due to limit studies, determining the concentration levels of BTXs in the oil-dependent industries is important, and carcinogenic quantitative risk estimation and non-carcinogenic assessment of exposed workers to BTXs in these industries are helpful for planning and taking work control measures. Since there are no published data on carcinogenic and non-carcinogenic quantitative risk assessment in the oil depot workers and these data are rare for petrochemical workers, this study was aimed to determine occupational exposure to BTXs and estimating the LCR and non- carcinogenic assessment of these chemical compounds using the HQ, in some petrochemical and oil depot workers in Iran.

MATERIALS AND METHODS

Study design

This cross-sectional study is conducted on 85 workers at petrochemical (34 subjects) and oil depot (51 subjects) industries of Iran in 2016. The sample size was calculated based on the concentration of benzene exposure among Iranian petrochemical workers and according to a study conducted by Rahimpour and colleagues (1.192 ± 0.639) using equation 1 ($\alpha=0.05$, $d=0.14$ and $\sigma=0.639$). According to the mentioned study, sample size estimated 80 subjects (30).

Equation 1)

$$n = \frac{(Z_{1-\alpha/2})^2 \times (\sigma^2)}{(d^2)}$$

The participant workers in our study were asked to disclose their demographic and occupational characteristics and smoking habits in a questionnaire form. Also, they were selected randomly by workers who have work experience of two years or more and without any history of smoking and employment in the second job with exposure to BTXs compounds. This study was approved by the Ethical Committee of Shiraz University of Medical Sciences, Shiraz, Iran. All the participants filled out the informed consent and signed it.

Personal air sampling

In order for determining the concentrations of benzene, toluene, and xylene isomers (ortho-, meta- and para-xylene) in the breathing zone of workers, individual sampling was performed according to the national institute for occupational safety and health (NIOSH) 1501 method, using the charcoal tube (bipartite derived from coconut 50/100 Manufactured by SKC Co) and a SKC sampling pump [31]. Before sampling, charcoal tube ends were broken and connected to a calibrated pump with a flow rate of 200 ml/min. Then charcoal tubes were attached to the collar of workers using holders, and sampling was carried out from the breathing zone air. After completion of the sampling period, tubes were detached and the two ends of the absorber tubes were closed by plastic caps and moved to the laboratory for preparation and analysis.

Sample preparation and analysis

In order for preparing air samples, at first, the front section of the charcoal tube was broken, then activated carbon absorbent containing absorbed contaminants was transferred into 4 ml vials. For extracting BTXs compounds, 1 ml of GC-grade carbon disulfide (CS₂) (Merck Co) was added to the vial of the activated charcoal absorbent. In order to transfer BTXs from activated carbon absorbent to carbon disulfide solvents, the vial door was firmly closed and was enclosed in an ultrasonic bath (Soltec 2200 MH model) for 30 min. After preparing the

solution, 1 μ L of it was injected into the port of gas chromatography (GC) [31].

The analysis was performed using GC (SCION-455GC) equipped with an FID detector using a capillary column (RTX, 624 with 25m 0.22mm 0.25mm). Helium (99.999%) was used as the carrier gas at a flow rate of 1.5 ml/min. The injector was set in the splitless mode and the temperature of it was set at 180°C. The column temperature program was set at 30°C initially, then increased to 180°C at 20°C/min and held for 30 Sec. Each chromatography's run was completed in 8 min.

Sampling and analytical quality control

In order to control breakthrough of the Sorbent tubes, front and back sections of the tubes were analyzed separately, and samples which the concentration of BTXs in the back section was more than the front section, 10%, were recognized as invalid samples, and for the samples of less than 10%, corrections were performed according to the NIOSH 1501 method formulas. In order to remove errors in sampling and analysis, blank samples were considered as constant as the obtained samples and all sampling and preparation steps were conducted similarly. The amount of analytical method recovery was tested by injection 2, 4, 6, 8 and 10 μ g of standard solutions to 5 charcoal tubes. The average recovery was given in 94% (91-101 percent). The calibration curves were plotted using injection different concentrations of 6 standard samples of each compound into the GC device [31].

Lifetime Cancer Risk (LCR) and Hazard Quotient (HQ) Estimation

Carcinogenic risk (LCR) and non-carcinogenic risk (HQ) were calculated using the method provided by the US EPA (32, 33).

LCR was calculated by multiplication of the chronic daily intake (CDI) by the slope factor for Benzene (Equation 2).

Equation 2)

$$LCR = CDI \times SF$$

The slope factor is an upper level, with a 95% confidence interval, on the increased cancer risk from a lifetime exposure to a chemical through ingestion or inhalation (mg/kg-day). The slope factor of benzene through inhalation was obtained from the California Environmental Protection Agency (0.1 mg/kg-day) [34].

CDI is the amount of absorbed chemical through the human body for the duration of working life. CDI be identified using Equation 3.

Equation 3)

$$CDI = \frac{(C_{adj-24h} \times IR \times ED \times EF)}{(BW) \times (AT) \times (NY)}$$

Where $C_{adj-24h}$ is the pollutant concentration in inhalation for 24 hours in day (mg/m^3), IR is the rate of inhalation (m^3/day), ED is the exposure duration (years), EF is the exposure frequency (days per year), BW is the body weight (kg), AT is the average time and NY is the number of days per year. In this study, the inhalation rate (IR) and body weight (BW) were considered $20m^3/day$ and $70kg$, respectively. The average time (AT) was reckoned 70 years for carcinogens and 30 years for non-carcinogens. The exposure duration (ED) and exposure frequency (EF) were considered 30 years and 240 days, respectively [32].

For calculating non-carcinogenic risk, the hazardousness through inhalation was measured by calculating the HQ using Eq. (4).

$$HQ = \frac{CDI}{RFD} \quad \text{Equation 4}$$

Where CDI is the chronic daily intake of non-carcinogenic substances ($mg/kg\text{-}day$) and RFD is the reference dose factor ($mg/kg\text{-}day$). In general, the RFD is a value to estimate a daily exposure for individuals who are liable to be without risks of injurious effects for their lifetime (including sensitive subgroups). In the other words, the RFD is the proportion of the No-Observable Averse Effect Level (NOAEL) over the Uncertainty Factor (UF) [33].

RFD for each compound was calculated using Eq. (5)

$$RFD = \frac{RFC \times IR}{BWa} \quad \text{Equation 5}$$

Where RfC is the reference concentration factor (mg/m^3), IR is the rate of inhalation (set at $20 [m^3/day]$), BW is the body weight (set at $70 [kg]$).

The RFC of benzene, toluene, and xylenes (m, o, p-isomers) obtained from the California Environmental Protection Agency (0.003 , 0.3 and $0.7mg/m^3$, respectively) [34].

Statistical analysis

Data were analyzed using SPSS (Chicago, Illinois, USA). The distribution of parameters was examined with Shapiro wilk test. Independent two-sample t-test was conducted for comparing mean concentrations of BTXs compounds between petrochemical and petroleum depot workers. In all tests, the level of significance was set at $P < 0.05$.

RESULTS

The demographic and job characteristics of petrochemical and oil depot workers are presented in Table 1. The mean (Std. Deviation) of age and Work experience of subjects were 32.41 (4.97) and 8.14 (4.38) respectively.

Table 1: occupational and demographic characteristics of petrochemical and oil depot workers

Industry		Mean	Std. Deviation	Min	Max
Petrochemical (n=34)	Age (year)	32.5	5.06	24.00	43.00
	Work experience (year)	7.29	5.24	2.00	22.00
	Height (cm)	175.47	4.65	169.00	187.00
	Weight (kg)	80.38	8.52	66.00	100.00
Petroleum depot (n=51)	Age (year)	31.35	4.95	22.00	42.00
	Work experience (year)	8.70	4.50	1.00	19.00
	Height (cm)	178.17	4.93	165.00	188.00
	Weight (kg)	81.27	9.05	65.00	95.00
Total (n=85)	Age (year)	32.41	4.97	22.00	43.00
	Work experience (year)	8.14	4.83	1.00	22.00
	Height (cm)	177.09	4.97	165.00	188.00
	Weight (kg)	80.91	8.80	65.00	100.00

Exposure concentrations of the BTXs compounds in both petrochemical and oil depot workers' groups, and also statistical differences between them are shown in Table 2. The mean concentration of benzene in the oil depot workers group was higher than the petrochemical workers, but this difference was not statistically significant ($P = 0.162$). Also, the mean concentration of benzene in the oil depot

workers group ($2.1 \pm 2.53mg/m^3$) was higher than the occupational exposure limits provided by the American conference of governmental industrial hygienists ($ACGIH_TLV = 1.67mg/m^3$). The measurement results of workers' exposure to toluene and xylenes (ortho-xylene, methyl-xylene and p-xylene) in the petrochemical and oil depot, showed that the mean concentrations of toluene, ortho-

xylene, methyl-xylene and p-xylene in both groups were lower than the limit values recommended by the ACGIH (ACGIH_TLV = 75.37mg/m^3 and 435mg/m^3 , for toluene and xylenes, respectively). The mean concentration of toluene in the exposed workers of the oil depot ($46.81 \pm 22.43\text{mg/m}^3$) was higher than the exposed workers of petrochemical ($41.83 \pm 30.06\text{mg/m}^3$), but this difference was not statistically significant ($P = 0.412$).

Unlike the benzene and toluene, the mean concentration of xylenes in the exposed workers of the petrochemical ($122.98 \pm 116.87\text{mg/m}^3$ and $121.76 \pm 95.96\text{mg/m}^3$ for o, m-xylene and p-xylene, respectively) was higher than the exposed workers of oil depot ($88.71 \pm 77.99\text{mg/m}^3$ and $95.18 \pm 76.08\text{mg/m}^3$ for o,m-xylene and p-xylene, respectively), but the differences were not statistically significant ($P = 0.139$ and $P = 0.159$ for o,m-xylene, and p-xylene, respectively).

Table 2: Concentrations of BTXs among the petrochemical and oil depot workers and statistical differences between both groups (mg/m^3)

		Mean	Std. Deviation	Minimum	Maximum	P-Value
Benzene	Petrochemical workers	1.49	1.31	0.03	4.45	0.162
	Petrochemical depot workers	2.1	2.53	0.008	14.23	
Toluene	Petrochemical workers	41.83	30.06	0.17	112.43	0.412
	Petrochemical depot workers	46.81	22.43	0.02	79.80	
O, m-Xylene	Petrochemical workers	122.98	116.87	14.40	412.50	0.139
	Petrochemical depot workers	88.71	77.99	1.90	321.50	
P- Xylene	Petrochemical workers	121.76	95.96	4.12	459.87	0.159
	Petrochemical depot workers	95.18	76.08	2.70	341.80	

The results of carcinogenic and non-carcinogenic risk assessment of BTXs compounds for the petrochemical and oil depot workers are given in Table 3. These results indicated a high risk in both of the study groups. The mean lifetime cancer risk of benzene in the oil depot workers was higher than the petrochemical workers ($1.681\text{E-}3$ and $1.163\text{E-}3$, for the oil depot and petrochemical, respectively). The mean lifetime cancer risk of benzene in both groups was higher than the reference value (Reference value:

1×10^{-6}). The results of average non-carcinogenic risk of BTXs showed that the HQ value of these compounds in both groups was higher than the reference value and the highest value was for the xylene (Reference value: $\text{HQ} < 1$). HQ values of benzene and toluene in the petrochemical workers were higher than the oil depot workers, while the HQ values of o, m-xylene, and p-xylene in the petrochemical workers were higher than the oil depot workers.

Table 3: Lifetime Cancer risk (LCR) and hazard quotient (HQ) related to BTXs compound's in Petrochemical and Petroleum depot workers

	Carcinogenic Risk (LCR)			Non-carcinogenic Risk (HQ)		
	Total	Petrochemical	Petrochemical depot	Total	Petrochemical	Petrochemical depot
Benzene	$1.474\text{E-}3$	$1.163\text{E-}3$	$1.681\text{E-}3$	13.84	10.91	15.78
Toluene	-	-	-	1.96	1.83	2.05
O, m-Xylene	-	-	-	221.17	265.56	191.57
P- Xylene	-	-	-	228.49	262.93	205.53

DISCUSSION

According to our knowledge, there is no survey on the carcinogenic and non-carcinogenic risk assessment of BTXs that has conducted on exposed workers of both petrochemical and oil depot at the same time. The results showed that oil depot workers have higher levels of exposure to benzene and toluene, in comparing with the petrochemical. Also, the average occupational exposure to benzene for both groups of workers was higher than the occupational exposure limits recommended by the Iranian Ministry of Health and Medical Education and ACGIH organization. Also, the results of the carcinogenic and non-carcinogenic risk assessment of

BTXs indicated a high-risk level in both groups. The mean lifetime carcinogenic risk of benzene in both groups was greater than the reference value. Furthermore, despite the lower average occupational exposure to toluene and xylenes, risk assessment results indicated much higher value than the reference value.

In this study, the mean exposure level of benzene in most of the workers was higher than the permissible limits, however, the mean exposure levels of toluene and xylenes were lower than the occupational exposure limits. There are some studies that have surveyed occupational exposure levels to BTXs in the petrochemicals and oil depots industries. Determined

values in these studies are different together and most of these values are lower than the obtained values of the present study. Chan *et al.* have determined mean exposure to benzene and toluene in Taiwan petrochemical industries, 0.0466mg/m^3 , and 0.177mg/m^3 , respectively [35]. Lerner *et al.* have determined the concentrations of benzene, toluene, p,m-xylene and ortho-xylene in the ambient air of Argentina petrochemicals, 0.016mg/m^3 , 0.021mg/m^3 , 0.012mg/m^3 and 0.0027mg/m^3 , respectively [36]. The difference of BTXs concentrations in this study and the cited studies may be explained by the dissimilarity of sampling methodology and probably more properly controlling measures in Taiwan and Argentina petrochemical industries than Iranian petrochemicals. In the studies carried out by Chan *et al.* and Lerner *et al.*, determining the compound concentrations was performed utilizing passive sampling and continuous monitoring system, respectively. However, in this study, determining the amounts of samples was performed using the NIOSH 1501 method. Thus, the difference of sampling methods used for evaluating occupational exposure to compounds may cause different results.

Also, some studies have conducted in Iran in order for evaluating occupational exposure to BTXs in petrochemical and oil depot industries. Azari *et al.* have determined occupational exposure to benzene in Tehran's oil depots 0.491 to 5.2mg/m^3 and the mean exposure to toluene 0.76 to 10.25mg/m^3 [15]. Also, they have determined the mean exposure to benzene higher than the occupational exposure limit, and the mean exposure to toluene lower than the occupational exposure limit, that these findings were consistent with the present study. Furthermore, they concluded that the concentration of xylene was lower than the detection limit, which this finding is in contradiction to our study, which the amounts of xylene were not lower than the detection limit in any sample. Rahimnejad *et al.* has surveyed levels of exposure to BTXs in southern Iranian oil fields which the mean levels of occupational exposure in their study were mostly lower than the present study. In their study, the exposure levels of benzene, toluene, ortho and metaxylene, and p-xylene were 0.236 to 1.323mg/m^3 , 0.09 to 0.877mg/m^3 , 0.144 to 1.49mg/m^3 , 0.047 to 1.185mg/m^3 , respectively [24]. Also in other studies conducted in Iran's petrochemicals, the resulted occupational exposure levels were less than the present study [22, 23]. The causes of the differences are not clear but may be rooted in the taken controlling measures in the present study in comparison with the other, differences in equipment maintenance in the present study with other studies which in turn determines a number of compounds leakage to air. Also differences between the present

study and Rahimnejad *et al.* study may be due to the amounts and produced compounds, and the differences between our study and the Azari *et al.* study may be due to rates of loading petroleum products in the investigated oil depots.

The results of evaluating the carcinogenic and non-carcinogenic risk of BTXs in both investigated groups showed high exposure risk. Mean LCR values were higher than the reference value in both groups. Furthermore, mean HQ value of BTXs in both groups was higher than the reference value and the most HQ value was related to xylenes.

The carcinogenic effect of benzene, and non-carcinogenic effects of BTXs, such memory, behavior and balance disorders, renal effects, liver effects, and central nervous system injury, have been proven through many studies. Chan *et al.* and Lerner *et al.* have determined the lifetime cancer risk in separate studies in petrochemical workers exposed to benzene, 1.4×10^{-5} and 5×10^{-5} , respectively [35, 36]. Also, Rahimnejad *et al.* have determined this value of 2.83×10^{-4} , which in all of the mentioned studies LCR value was lower than the present study [24].

There are several studies dealt with the hazards, and the prevalence of some diseases in the oil depot workers, while there is no study surveying carcinogenic and non-carcinogenic risk of exposing to BTXs in oil depot workers. Anthony *et al.* in two separate studies has reported Liver and cardiovascular diseases among the oil depot workers [37, 38]. Also, LI Li-Chun *et al.* have examined the occupational hazards in oil depots, which one of the most important hazards was exposure to high-level benzene that is consistent with the findings of the present study [39]. According to Anthony *et al.* study, the prevalence of liver and cardiovascular diseases in the oil depot workers can be related to the non-carcinogenic risk of exposing chemical compounds, which are consistent with high-level non-carcinogenic risk in the present study. In the other study conducted by LI Zheng-hong *et al.* in some oil depots of China, the non-carcinogenic risk of exposure to toluene and benzene was in the acceptable limit, which is in contrast to the present study [40]. The most significant cause of this difference may be explained by the different investigated exposure way. LI Zheng-hong *et al.*, have surveyed pollution of groundwater with BTXs, and they have estimated the non-carcinogenic risk through the oral way, while in the present study it estimated through inhalation way.

Generally, the findings of the present study imply high-risk of carcinogenic and non-carcinogenic effects of occupational exposure to BTXs in petrochemical and oil depot workers, and control measures in order for reducing occupational

exposures, can be taken. It is recommended for further studies to consider exposure to the other chemical compounds simultaneously and also determining the carcinogenic and non-carcinogenic effects and the prevalence of related disease can be surveyed in order to achieve more realistic information.

CONCLUSION

The LCR of benzene, and HQ of benzene, toluene, o,m-xylene, and p-xylene in the both investigated groups, petrochemical and oil depot workers, were higher than the reference values, and in some cases, these values were higher in the oil depot workers than the petrochemical workers. In order to reduce the occupational exposure of workers to BTXs in the investigated oil depot and petrochemical, control measures should be taken in future, as soon as possible.

ETHICAL ISSUES

This study was approved by Ethical Committee of Shiraz University of Medical Sciences, Shiraz, Iran

CONFLICT OF INTEREST

The authors declare that they have no conflicts of interest.

AUTHORS' CONTRIBUTION

All authors worked equally. All authors have contributed to the review and finalization of this manuscript. All authors read and approved the manuscript.

FUNDING/ SUPPORTS

This study was approved by Vice-Chancellor of Education and funded by the Vice-Chancellor for Research and Technology, Shiraz University of Medical Sciences-Faculty of Larestan (Grant no. 1147).

ACKNOWLEDGEMENT

The authors acknowledge the financial support of Shiraz University of Medical Sciences for this work.

REFERENCES

[1] Snodgrass WR. Petroleum Industry. In: Greenberg, Michael I, editors. Occupational, Industrial, and Environmental Toxicology. 2 ed: Mosby; 2003.

[2] Sarigiannis DA, Karakitsios SP, Gotti A, Liakos IL, Katsoyiannis A. Exposure to major volatile organic compounds and carbonyls in European indoor environments and associated health risk. *Environment international*. 2011;37(4):743-65.

[3] Nurmatov UB, Tagiyeva N, Semple S, Devereux G, Sheikh A. Volatile organic compounds and risk of asthma and allergy: a systematic review. *Eur Respir Rev*. 2015;24(135):92-01.

[4] Rumchev K, Brown H, Spickett J. Volatile organic compounds: do they present a risk to our health? *Rev Environ Health*. 2007;22(1):39-56.

[5] Wang F, Liu F, Liu H, Chen W, Si X, Ma X. Effects of immunological and hematological parameter in mice exposed to mixture of volatile organic compounds. *Inhal Toxicol*. 2016;28(4):164-69.

[6] Win-Shwe, T.-T., Fujimaki, H., Arashidani, K., & Kunugita, N. Indoor Volatile Organic Compounds and Chemical Sensitivity Reactions. *Clinical and Developmental Immunology*, 2013:1-8, doi:10.1155/2013/623812

[7] Baan R, Grosse Y, Straif K, Secretan B, El Ghissassi F, Bouvard V, *et al*. A review of human carcinogens—part F: chemical agents and related occupations. *Lancet Oncol*. 2009;10(12):1143-44.

[8] International Agency for Research on Cancer. IARC monographs on the evaluation of carcinogenic risks to humans: volume 100 F-A review of human carcinogens. France: WHO Press; 2012.

[9] World Health Organization. Air quality guidelines for Europe. WHO Regional Publications, European Series No. 23. Copenhagen, Denmark: World Health Organization; 2000.

[10] Ciarrocca M, Tomei G, Fiaschetti M, Caciari T, Cetica C, Andreozzi G, *et al*. Assessment of occupational exposure to benzene, toluene and xylenes in urban and rural female workers. *Chemosphere*. 2012;87(7):813-19.

[11] Lerner JC, Sanchez E, Sambeth J, Porta A. Characterization and health risk assessment of VOCs in occupational environments in Buenos Aires, Argentina. *Atmos Environ*. 2012;55:440-47.

[12] Majumdar D, Dutta C, Mukherjee A, Sen S. Source apportionment of VOCs at the petrol pumps in Kolkata, India; exposure of workers and assessment of associated health risk. *Transp Res D Transp Environ*. 2008;13(8):524-30.

[13] Navasumrit P, Chanvaivit S, Intarasunanont P, Arayasiri M, Lauhareungpanya N, Parnlob V, *et al*. Environmental and occupational exposure to benzene in Thailand. *Proceedings of the International Symposium on Recent Advances in Benzene Toxicity*; 2004 9-12 October, Munich, Germany: Chem Biol Interact.

[14] Tompa A, Jakab MG. Risk management among benzene-exposed oil refinery workers. *Int J Hyg Environ Health*. 2005;208(6):509-16.

[15] Azari MR, Konjin ZN, Zayeri F, Salehpour S, Seyedi M. Occupational exposure of petroleum depot

workers to BTEX compounds. *Int J Occup Environ Med.* 2011;3(1):39-44.

[16] Bahrami A, Jonidi-Jafari A, Mahjub H. Environmental exposure to xylenes in drivers and petrol station workers by urinary methylhippuric acid. *J Res Health Sci.* 2008;8(2):61-68.

[17] Bahrami AR. Distribution of volatile organic compounds in ambient air of Tehran. *Arch Environ Health.* 2001;56(4):380-83.

[18] Bahrami AR, Joneidi Jafari A, Ahmadi H, Mahjub H. Comparison of benzene exposure in drivers and petrol stations workers by urinary trans, trans-muconic acid in west of Iran. *Ind health.* 2007;45(3):396-01.

[19] Ebrahemzadih M, Abadi ABF, Giahi O, Tahmasebi N. Exposure Assessment to Benzene, Toluene, Ethyl Benzene and Xylene (BTEX) in Gas Stations in Central Region of Iran. *Asian J Water Environ Pollut.* 2016;13(1):43-48.

[20] Hazrati S, Rostami R, Fazlzadeh M, Pourfarzi F. Benzene, toluene, ethylbenzene and xylene concentrations in atmospheric ambient air of gasoline and CNG refueling stations. *Air Qual Atmos Health.* 2016;9(4):403-09.

[21] Negahban AR, Ghorbani Shahna F, Rahimpour R, Jalali M, Rahiminejad S, Soltanian A, *et al.* Evaluating Occupational Exposure to Carcinogenic Volatile Organic Compounds in an Oil-Dependent Chemical Industry: a Case Study on Benzen and Epichlorohydrin. *Journal of Occupational Hygiene Engineering.* 2014;1(1):36-46 [Persian].

[22] Maghsoodi Moghadam R, Bahrami A, Ghorbani F, Mahjub H, Malaki D. Investigation of qualitative and quantitative of volatile organic compounds of ambient air in the Mahshahr petrochemical complex in 2009. *J Res Health Sci.* 2013;13(1):69-74.

[23] Rahimpour R, Bahrami A, Assari M, Ghorbani F, Negahban A, Rahiminejad S, *et al.* Biological monitoring of petrochemical industry workers exposed to benzene, toluene, xylenes, methyl ethyl ketone, and phenol in Southern Iran. *Journal of Occupational Health and Epidemiology.* 2014;3(2):62-71.

[24] S Rahiminejad., A Bahrami., M Assari., A Sultanian., R Rahimpour., A Negahban., *et al.* Quantitative risk assessment of occupational exposure to Volatile Organic Compounds in the oil-dependent chemical industry. *J Sabzevar Univ Med Sci.* 2014;21(4):829-41 [Persian].

[25] Beheshti M, Firoozi CA, Alinaghi LA, Rostami S. Semi-quantitative risk assessment of health exposure to hazardous chemical agents in a petrochemical plant. *J Occup Health Epidemiol.* 2015;4(1):1-8.

[26] Golbabaie F, Eskandari D, Rezazade Azari M, Jahangiri M, Rahimi M, Shahtaheri J. Health risk

assessment of chemical pollutants in a petrochemical complex. *Iran Occupational Health Journal.* 2012;9(3):11-21 [Persian].

[27] Jahangiri M, Jalali M, Saeidi C, Mohammadpour H, Mardi H, Mehr Alipour J. Health Risk assessment of occupational harmful chemicals in order to provide Control guidelines: case study in a polyurethane foam industry. *TKJ.* 2013;5(4):33-41 [Persian].

[28] Jalali M, Jalali S, Shafii motlagh M, Mardi H, Negahban SAR, Faraji tomarkandi V, *et al.* Health risk assessment of occupational exposure to BTEX compounds in petrol refueling stations in Mashhad. . *J Neyshabur Univ Med Sci.* 2014;1(1):19-27 [Persian].

[29] Zare Jeddi M, Yunesian M, Ahmadkhaniha R, Kashani H, Rastkari N. Semi-Quantitative and Quantitative Health Risk Assessment of Gas Station Workers Exposure to Benzene. *Iranian Journal of Health and Environment.* 2015;8(3):391-400 [Persian].

[30] R Rahimpour, AR Bahrami, F Ghorbani, MJ Assari, AR Negahban, S Rahiminejad, *et al.* Evaluation of Urinary Metabolites of Volatile Organic Compounds and Some Related Factors in Petrochemical Industry Workers. *J Mazandaran Univ Med Sci.* 2014;24(116):119-31 [Persian].

[31] NIOSH Manual of Analytical Methods (NMAM). Hydrocarbons, Aromatic: Method 1501. 4 ed. Cincinnati, OH: U.S: Department of Health and Human Services, Public Health Service, Centers for Disease Control; 2003.

[32] Ricci P. Environmental and health risk assessment and management: principles and practices. Netherlands.: Springer Science & Business Media; 2006. 370-75 p.

[33] United State Environmental Protection Agency (US EPA). Proposed Guidelines for Carcinogen Risk Assessment. Washington, DC: Office of Research and Development; 1996.

[34] California Environmental Protection Agency (CalEPA). Toxicity Criteria Database California Office of Environmental Health Hazard Assessment (OEHHA); 2017 [1.11.2017]. Available from: <http://oehha.ca.gov/chemicals>.

[35] Chan C-C, Shie R-H, Chang T-Y, Tsai D-H. Workers' exposures and potential health risks to air toxics in a petrochemical complex assessed by improved methodology. *Int Arch Occup Environ Health.* 2006;79(2):135-42.

[36] Lerner JEC, Kohajda T, Aguilar ME, Massolo LA, Sánchez EY, Porta AA, *et al.* Improvement of health risk factors after reduction of VOC concentrations in industrial and urban areas. *Environ Sci Pollut Res.* 2014;21(16):9676-88.

[37] Egbunu ACC, Nkwazema DC. Dysfunctional Liver and other High Metabolic Organs in

Asymptomatic Petroleum Depot Workers in Calabar South-South, Nigeria. *Res J Environ Sci.* 2015;9(8):355-63.

[38] Egbuonu ACC, Nkwazema DC, Ezeanyika LU. Cardiovascular risks and impaired lipid metabolism in asymptomatic petroleum depot workers in Calabar Metropolis, Nigeria. *Res J Environ Sci.* 2015;9(6):270-79.

[39] LI L-c, GENG J-w, SU S-b. Analysis of Occupational Hazards and Key Control Points in Oil Depot. *Chinese Journal of Public Health Engineering.* 2010;10(02):128-37 [Chinese].

[40] Li Z-H, Zhang S, Bi E-P, Yu J, Wang W-Z, Ma L-S, *et al.* The health risk assessment of groundwater organic pollution at a certain oil depot. *Diqiu Xuebao(Acta Geoscientica Sinica).* 2010;31(2):258-62 [Chinese].